

A100R

**RELIABLE
POWERFUL
ROBUST**



apolloTM



PRODUCT SPECIFICATIONS

APOLLO A100R

DIMENSIONS AND WEIGHT		PERFORMANCE	
LENGTH	4.270 mm	THRUST/PULLBACK	5.000 kg
WIDTH	1.550 mm	MAX TORQUE	2.600 Nm
HEIGHT	2.000 mm	MAX SPINDLE SPEED	160 tpm
WEIGHT (WITHOUT DRILL PIPES)	4.340 kg		
WEIGHT (WITH DRILL PIPES)	4.928 kg		
ENGINE		FEATURES	
MAKE & MODEL	CAT® C2.2	ELECTRICAL SYSTEM	12Vdc
FUEL	Diesel	LIGHTS	Yes
MAX ENGINE RPM	2.200 tpm	CABIN	Canopy
NUMBER OF CYLINDERS	4	AIR CONDITIONING	-
HORSEPOWER	73 hp (55 kW)	HYDRAULIC ANCHORING SYSTEM	Yes
MAX TORQUE	270 Nm @ 1.600 tpm	RACK AND PINION	Yes
COOLING	Liquid	RADIO CONTROLLED UNDERCARRIAGE	Yes
EMISSION VALUE	EPA Tier IV Final (Euro Stage 5)	ROD LOADING SYSTEM	-
DRILL PIPES		HYDRAULIC SYSTEM	
LENGTH	1.829 mm (1,8 mtr)	AUXILIARY PUMP RELIEF PRESSURE	205 bar
OD TOOLJOINT	48 mm	PUSH/PULL PUMP RELIEF PRESSURE	230 bar
PIPE DIAMETER	42 mm	ROTARY PUMP RELIEF PRESSURE	230 bar
WEIGHT (PER PIPE)	18 kg		
ROD BOX CAPACITY	50 pieces		
MINIMAL BEND RADIUS	30 mtr		
BENTONITEPUMP		TANK CAPACITY	
CAPACITY	100 ltr/min	ENGINE OIL	10 ltr
PRESSURE	70 bar	DIESEL	100 ltr
		HYDRAULIC OIL	90 ltr
SAFETY FEATURES			
STRIKE-ALERT	Yes	REMOTE LOCK OUT	Yes
ANTI-FREEZE SYSTEM	Yes		

Although the product specifications have been compiled with care, no rights can be derived from them. Changes, printing and typesetting errors reserved.

© 2025 Rhino Supply. All rights reserved.

No part of this publication may be reproduced, distributed, stored and/or disclosed in any form without prior, written permission from Rhino Supply.